

CODE READER™ 4400



Features & Benefits

- Compatible with an Apple® iPhone® 5, 5s and SE; and iPod® 5th and 6th generation
- CodeShield™ Disinfectant ready plastics
- Dragontrail glass screen protection
- Lightweight design combines easy-to reach buttons with an unobstructed view of the iPhone® or iPod® screen
- Bright, rectangular, blue LED aiming quickly and easily targets and reads all barcodes
- Secure housing holds phone in place, protecting it against damage and minimizing exposure to debris
- Software Development Kit (SDK) assists in creating a custom scanner application
- Single and quad-bay charging station options

Cost-effectively and quickly convert your iPhone® or iPod® into a mobile barcode reading solution.

Consolidating technologies into one, user-friendly device has perhaps never been more in demand among mobile-driven applications, and the CR4400 sled is leading the way.

Ideal for fast-paced environments such as healthcare and retail, its sleek, ergonomic design features advanced imaging technology for increased productivity and mobile workflow efficiency.

Designed to protect your investment.

The CR4400 barcode reading sled is the only one that features replaceable, rechargeable battery cartridges. This makes changing depleted batteries quick and easy, and avoiding workflow interruptions even easier. Its durable housing withstands harsh environments, and consists of disinfectant ready plastics that stand up to frequent cleaning with rigorous chemicals. The CR4400 delivers superior performance on all 1D, 2D and stacked barcode symbologies, and it includes a software development kit to tailor scanner applications.

For speed, efficiency and versatility, the CR4400 sled steps up as the ultimate solution to multiple challenges.



Applications

Healthcare, retail, government, event management, field services

Features at a Glance



*Screen and keypad are available via iPhone.

CODE READER™ 4400 SPECIFICATIONS

Physical Characteristics

CR4400 Dimensions	5.75" L x 2.7" W x 1.0" D (146 mm L x 68 mm W x 25 mm D)
CR4400 Weight (w/ battery & phone)	12.0 oz (300.0g)
Charging Station Dimensions	4.6" L x 4.5" W x 2.7" H (117 mm L x 114 mm W x 69 mm H)
Charging Station Weight	5.3 oz (150.0g)

User Environment

Operating Temperature	0° to 35° C / 0° to 95° F
Storage Temperature	-20° to 45° C / -4° to 113° F
Humidity	5% to 95% non-condensing
Decode Capability	1D: BC412, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, IATA 2 of 5, Interleaved 2 of 5, GS1 DataBar, Hong Kong 2 of 5, Matrix 2 of 5, MSI Plessey, NEC 2 of 5, Pharmacoode, Plessey, Straight 2 of 5, Telepen, Trioptic, UPC/EAN/JAN Stacked 1D: Codablock F, Code 49, GS1 Composite (CC-A/CC-B/CC-C), MicroPDF, PDF417 2D: Aztec Code, Data Matrix, Data Matrix Rectangular Extension, Grid Matrix, Han Xin, Maxicode, Micro QR Code, QR Code, QR Model 1 Proprietary 2D: GoCode® (Additional License Required) Postal Codes: Australian Post, Canada Post, Intelligent Mail, Japan Post, KIX Code, Korea Post, Planet, Post-net, UK Royal Mail, UPU ID-tags
Image Output Options	Formats: JPEG or PGM
Field Selection	High Density or Wide Field
Time Stamp	Interval Logging
Data Editing	JavaScript (Additional License Required)

Working Ranges

CR4400 Performance

Test Barcode	Min Inches (mm)	Max Inches (mm)
3 mil Code 39	3.1" (80 mm)	4.0" (102 mm)
7.5 mil Code 39	1.3" (33 mm)	7.2" (182 mm)
10.5 mil GS1 DataBar	0.8" (20 mm)	8.7" (220 mm)
13 mil UPC	1.1" (28 mm)	11.0" (280 mm)
5 mil DM	1.7" (43 mm)	4.5" (115 mm)
6.3 mil DM	1.3" (33 mm)	5.9" (150 mm)
10 mil DM	0.8" (20 mm)	7.1" (180 mm)
20.8 mil DM	1.1" (28 mm)	13.5" (343 mm)

Note: Working ranges are a combination of both the wide and high density fields. All samples were high quality barcodes and were read along a physical center line at a 10° angle. Default AGC settings were used. Accuracy = +/- 10%.

Performance Characteristics

Field of View	High Density Field: 30° horizontal by 20° vertical Wide Field: 50° horizontal by 33.5° vertical
Focal Point	Approximately 100 mm
Sensor	CMOS 1.2 Megapixel (1280 x 960) gray scale
Optical Resolution	High Density Field: 960 x 640 Wide Field: 960 x 640
Pitch	± 65° (from front to back)
Skew	± 60° from plane parallel to symbol (side-to-side)
Rotational Tolerance	± 180°
Symbol Contrast	15% minimum reflectance difference
Target Beam	Single, blue targeting bar
Ambient Light Immunity	Sunlight: Up to 9,000ft-candles/96,890 lux
Shock	Without phone withstands multiple drops of 6' (1.8 Meters) to concrete With phone withstands multiple drops of 4' (1.22 meters) to concrete
Memory Capacity	128MB Flash ROM, 32MB RAM
Battery Capacity (without phone)	2,000 mAh
Communication Interfaces	USB, Wireless Interfaces Supported by iPhone 5/5s/SE and iPod Gen. 6
Operational Modes	iOS App Mode and iOS Keyboard Mode for iPhone and iPod
Warranty	www.codecorp.com/warranty

Accessories

- Lithium-Ion Battery
- Single and quad-bay charging stations
- Carrying case, wrist and shoulder lanyard



code
REVOLUTIONIZING BARCODE READING

Web: www.codecorp.com

